

TOLL FREE: 1-855-COM@COIL

(1-855-266-2645) Fax: 705.733.5652

Email: lucas@emccltd.com

SLIP RING DATA



Job#:	Keyway YES NO *Draw an arrow to Indicate Keyway Position in reference to the lead & ring #	Lead attached to Ring # () (*note ring #'s on bottom view) Web Vented Ring
HP: Amps: Volts: SLIP RING TYPE	Lead attached to Ring # () (*note ring #'s on bottom view)	Lead attached to Ring # () (*note ring #'s on bottom view)
☐ Refillable ☐ Cast ☐ Molded NUMBER OF RINGS:	Cooling Hole Ring Hub Length	Lead Ext. Length
RING MATERIAL Bronze Copper Other: KEYWAY SIZE:	Hub Ext.	Hub Ext.
ADDITIONAL SLIP RING DATA Spiral Grooved Recessed	LEAD	
LEAD TYPE Round Flat Wire NUMBER OF LEADS PER RING:	BORE DIA	Insulation Ring Dia. Ring Dia.
SIZE OF LEADS: LEAD MATERIAL Brass Copper Other:		
INSULATION BETWEEN RINGS Insulation Air Gap SHAFT DIAMETER:	Ring #1 Ring #2 Ring #	±3
ARE VENTING/COOLING HOLES REQUIRED YES NO	Spacing Ring Width Spacing	·