

TOLL FREE: 1-855-COM@COIL (1-855-266-2645)

Fax: 705.733.5652

Email: lucas@emccltd.com





CUSTOMER:	QUOTE#
ADDRESS:	
CITY: STATE:	EMAIL QUOTE TO:
	PHONE #
ZIP/POSTAL CODE	FAX #
CUSTOMER JOB#	NOTES:
CUSTOMER P.O. #	
CUSTOMER CONTACT:	
PHONE #	
MANUFACTURER:	MODEL: FRAME:
SPEED (R.P.M):	TYPE: STYLE:
VOLTAGE:	HP/KW: SN:
CURRENT (AMPS):	
1. CORE DIAMETER	TOTAL COIL LENGTH
2. CORE LENGTH	
3. COIL EXTENSION OPPOSITE CONNECTION END	COLLEXTENSION CONNECTION END SPINGER LENGTH CONNECTION END CONNECT
4. COIL EXTENSION CONNECTION END	CONNECTION TOTAL TOTAL
5. FINGER LENGTH	SLOT DEPTH
6. TOTAL COIL LENGTH	9 J
7. CLEARANCE OPPOSITE CONNECTION END	WOUND
8. CLEARANCE CONNECTION END	ROTOR 15 16 16 SKEWED SLOTS
9. FINGER TO FINGER	
10. TOTAL SLOT DEPTH	
11. SLOT WIDTH	
12. SEMI OPENING	SKEWED SLOTS
13. BELOW WEDGE	
14. SLOT WIDTH	
15. TOTAL SLOT DEPTH	\\\\\\
16. BELOW WEDGE	
17. SLOT WIDTH	
18. TOTAL SLOT DEPTH	— BAND
19. BELOW BAND	
NUMBER OF SLOTS:	OPPOSITE END: KNUCKLE or CLIP
COIL SPAN 1 AND:	
TURNS PER COIL:	LEADS BARE orTIN
COILS PER SLOT: WOUND: WAVE or LAP	WIRE ON EDGE or ON FLAT
WOUND: WAVE or LAP WIRE THICKNESS:	# OF WIRES IN HAND: COMMENTS:
WIRE WIDTH:	# OF WIRES HIGH
STRAND INSULATION:	CUSTOMER ACCEPTANCE? YES
# OF WIRES WIDE:	DATE:
INSULATION TYPE: V.P.I. or CURED	DAIL.
WEIGHT PER COIL:	-
T.E.SITT ER COIL.	